

iARENA SERIES

GPA-350S // SLEEVED // 350WATT



Product: PSU

Form factor: PSII

Color: silver

The lowest wattage power supply in the iARENA Series also complies to the latest RoHS and WEEE (2002/95/EG) guidelines and is designed for the assemblers in the first instance.

Certificates:



Technical data

Specification:	ATX 12V 2.3
Efficiency:	< 80%
Dimensions (DxWxH):	140mm x 150 mm x 87 mm
PCF:	Active PFC (0,9)
Fan:	120mm silent fan

Connectors

20+4 PIN	8PIN EPS	4PIN 12V	SATA	Molex	Floppy	8PIN PCIe (6+2)	6PIN PCIe
1	0	1	3	2	1	0	0

DC Output / AC Input

AC INPUT: 230V /4A FREQUENCY: 50HZ MAX. LOAD: 350W	DC OUTPUT								
	+5V	+3,3V	+12V1	+12V2	+12V3	+12V4	P.F.	-12V	+5VSB
	17A	21A	15A	15A	N/A	N/A	>0,9	0,3A 3,6W	2,5A 12,5W
	110W		300W		N/A				

Security: UVP; OVP; SCP; OPP; AFC

The listed specifications may be altered at any point in time without any pre-notice. Chieftec® is a registered trade mark. All other brands and/or logos are property of the respective owners.