

# REDUNDANT

MRT-5450G // SLEEVED // 450WATT



**Product:** PSU

**Form factor:** PSII

**Color:** silver

If you are looking for "green-power" and high-performance 24-7, then the MRT-5450G will be the choice.

**Certificates:**



## Technical data

**Specification:** ATX 12V 2.3

**Efficiency:** >90%

**Dimensions (DxWxH):** 185mm x 150 mm x 87 mm

**PCF:** Active PFC (0,9)

**Fan:** 40mm fan (2x 40mm per module)

## Connectors

24 PIN	8PIN EPS	System LED	SATA	Molex	Floppy	TTL Signal Kabel	Buzzer
1	1	0	4	7	1	1	1
8PIN EPS (4+4)	6PIN PCIe	8 PIN PCIe (6+2)					
1	0	0					

## DC Output / AC Input

AC INPUT: 100V / 7A 240V / 3A  FREQUENCY: 47 - 63 HZ  MAX. LOAD: 450W	DC OUTPUT								
	+5V	+3,3V	+12V1	+12V2	+12V3	-5V	P.F.	-12V	+5VSB
	25A	25A	37A	N/A	N/A	N/A	>0,9	0,5A	3,0A
	150W		N/A						

## Security:

Met.al frame, 2x 450W modules, TTL-Signal, Buzzer- LED Alarm, hot-swap, hot-plug features, full range Input 100V~240V, Meet FCC, CISPR EMI regulation, Balanced load sharing design, UVP; OVP; SCP; OPP; OCP; OTP; AFC

The listed specifications may be altered at any point in time without any pre-notice. Chieftec® is a registered trade mark. All other brands and/or logos are property of the respective owners.