

REDUNDANT

MRT-6320P // SLEEVED // 350WATT



Product: PSU

Form factor: PSII

Color: silver

24 hours - 7 days - 52 weeks; This is what the MRT-6320P will offer you. Non-stop performance on the highest level with the highest efficiency for SMB servers.

Certificates:



Technical data

Specification: ATX 12V 2.3

Efficiency: < 80%

Dimensions (DxWxH): 185mm x 150 mm x 87 mm

PCF: Active PFC (0,9)

Fan: 40mm fan (2x 40mm per module)

Connectors

24PIN	8PIN EPS (4+4)	4PIN 12V	SATA	Molex	Floppy	TTL Signal Kabel	Buzzer
1	0	1	2	8	2	1	1

DC Output / AC Input

AC INPUT: 100V / 6A 240V / 3A FREQUENCY: 50 - 60 HZ MAX. LOAD: 320W	DC OUTPUT								
	+5V	+3,3V	+12V1	+12V2	+12V3	-5V	P.F.	-12V	+5VSB
	25A	18A	15A	N/A	N/A	0,5A	>0,9	0,5A	2A
	35A max.		+5V, 3,3V, 12V1 combi. / 302W		N/A				

Security:

Met.al frame, 2x 320W modules, TTL-Signal, Buzzer- LED Alarm, hot-swap, hot-plug features, full range Input 100V~240V, Meet FCC, CISPR EMI regulation, Balanced load sharing design, UVP; OVP; SCP; OPP; OCP; OTP; AFC

The listed specifications may be altered at any point in time without any pre-notice. Chieftec® is a registered trade mark. All other brands and/or logos are property of the respective owners.