

iARENA SERIES

GPA-450S // SLEEVED // 450WATT



Product: PSU

Form factor: PSII

Color: silver

An approximate lifecycle of >100.000 hours can be expected from this GPA-450S which makes it a reliable choice for continuous and cost-saving operation.

Certificates:



Technical data

| | |
|----------------------------|------------------------|
| Specification: | ATX 12V 2.3 |
| Efficiency: | < 80% |
| Dimensions (DxWxH): | 140mm x 150 mm x 87 mm |
| PCF: | Active PFC (0,9) |
| Fan: | 120mm silent fan |

Connectors

| 20+4 PIN | 8PIN EPS | 4PIN 12V | SATA | Molex | Floppy | 8PIN PCIe (6+2) | 6PIN PCIe |
|----------|----------|----------|------|-------|--------|-----------------|-----------|
| 1 | 0 | 1 | 3 | 2 | 1 | 1 | 0 |

DC Output / AC Input

| | | | | | | | | | |
|--|-----------|-------|-------|-------|-------|-------|------|--------------|---------------|
| AC INPUT: 230V /4A FREQUENCY: 50HZ MAX. LOAD: 450W | DC OUTPUT | | | | | | | | |
| | +5V | +3,3V | +12V1 | +12V2 | +12V3 | +12V4 | P.F. | -12V | +5VSB |
| | 18A | 22A | 21A | 18A | N/A | N/A | >0,9 | 0,3A 3,6W | 2,5A 12,5W |
| | 120W | | 360W | | N/A | | | | |

Security: UVP; OVP; SCP; OPP; AFC

The listed specifications may be altered at any point in time without any pre-notice. Chieftec® is a registered trade mark. All other brands and/or logos are property of the respective owners.