

SMART SERIES

PSF-400A // SLEEVED // 400WATT



Product: PSU

Form factor: PSII

Color: silver

Nowadays, system integrators besides a durable chassis, require a reliable and stable power source for its UNC (IPC) chassis. The PSF-400A of CHIEFTEC matches and exceeds this requirements. Being a reliable power source for all UNC cases ranging from the 2U way up to the 5U, its constructed for every possible installation...

Certificates:



Technical data

Specification: ATX 12V 2.3

Efficiency: < 80%

Dimensions (DxWxH): 140 mm x 150 mm x 87 mm

PCF: Active PFC

Fan: 80mm fan

Connectors

24PIN	8PIN EPS (4+4)	SATA	Molex	Floppy	6PIN PCIe		
1	1	4	3	1	1		

DC Output / AC Input

AC INPUT: 115V - 230V / 5A FREQUENCY: 50 - 60HZ MAX. LOAD: 400W	DC OUTPUT								
	+5V	+3,3V	+12V1	+12V2	+12V3	+12V4	P.F.	-12V	+5VSB
	20A	24A	18A	18A	N/A	N/A	>0,9	0,3A 3,6W	2,5A 12,5W
	120W		300W		N/A				

Security: UVP; OVP; SCP; OPP; AFC;

The listed specifications may be altered at any point in time without any pre-notice. Chieftec® is a registered trade mark. All other brands and/or logos are property of the respective owners.