

- **4-PIN PWM fan-speed control and 3-PIN +5V A-RGB M/B-Sync Technologies supported**
- **Low noise & perfect illumination**
- **Optimized Air Flow**



Introducing **CHIEFTEC's ZF-1425RGB**, our fan aims to deliver optimal illumination performance with well-balanced maximal airflow and minimal noise disruption.

Take command of your cooling experience with the inclusion of a 4-PIN PWM fan-speed control and seamless compatibility with 3-PIN +5 A-RGB M/B Sync Technologies.

ZF-1425RGB is ready to elevate your setup for an exceptional user experience.



TECHNICAL DATA	
Model	ZF-1425RGB
EAN Code	0753263078827
Connector	Fan: 4 pin PWM ; A-RGB: 3 pin
Dimension (mm)	140 x 140 x 25
Weight (without/with package)	135g / 165g
Bearing Type	Hydraulic
LED Type	Addressable RGB
LED Lamp	26 pcs (Inner Ring: 8 pcs ; Outer Ring: 18pcs)
Rated Voltage	FAN: DC12V ; LED: DC5V
Rated Current	0.28A (Max: 0.38A)
Operating Voltage	9.0V - 12V
Fan Speed (RPM)	600 - 1600 RPM \pm 10%
Air Flow (CFM)	48.2 CFM
Air Pressure (mmH2O)	1.09 mmH2O
Noise Level (dBA)	25.8 dBA
Scope of delivery	1x 140mm A-RGB fan, 4x Mounting screws
RGB Sync Compatibilities	Support and sync the lighting with: ASUS™ AURA SYNC, MSI™ MYSTIC LIGHT SYNC, ASROCK™ POLYCHROME SYNC, GIGABYTE™ RGB FUSION
Warranty	24 Months

*The listed specifications may be altered at any point in time without any pre-notice.

Version: 12/2024

**Chieftec® is a registered trademark. All other brands and/or logos are property of the respective owners.