

- > 9 blade design with enhanced air pressure technology
- > Dual-Ring setup for perfect illumination inside and out
- > 32 addressable LEDs offering complex RGB effects
- > 4-PIN PWM fan-speed control and 3-PIN +5V A-RGB M/B-Sync

Technologies supported

CHIEFTRONIC's NOVA RGB Fan comes with beautiful A-RGB illumination from a dual-ring design to ensure smooth and full lighting with 16 LED's on the inner ring as well as 16 more LED's on the outer ring. Additional frame design elements on the outer ring ensure the Nova fan stands out from the crowd and impress visually.

The single fan comes with 4-PIN PWM connector to power and control the fan speed via the motherboard, as well as a 3-PIN +5V A-RGB connector to allow for control via most mainstream motherboard sync technologies like ASUS™ AURA SYNC, MSI™ MYSTIC LIGHT SYNC, ASROCK™ POLYCHROME SYNC, GIGABYTE™ RGB FUSION.

Translucent fan blades ensure lighting transfers evenly throughout the entire fan, while anti-vibration pads ensure smooth and quiet operation.



Technical data

Model	NF-1225RGB
EAN Code	0753263077257
Connectors	Fan: 4 pin PWM ; ARGB: 3 pin
Dimension	120 mm x 120 mm x 25 mm
Weight (N./W./ G.W.)	135g / 145g
Bearing Type	Hydraulic
LED Type	Addressable RGB (A-RGB)
LED Count	32 pcs (Inner Ring: 16 pcs ; Outer Ring: 16pcs)
Rated Voltage	FAN: DC 12V ; LED: DC 5V
Rated Current	0.29A (Max: 0.65A)
Operating Voltage	7V -13.2V
Fan Speed (RPM)	1600 RPM ± 10%
Air Flow (CFM)	68 CFM
Air Pressure (mmH2O)	2.2 mmH2O
Noise Level (dBA)	24 dBA (Max: 28)
Scope of delivery	1x 120mm RGB Rainbow fan, 4x Mounting screws
RGB Sync Compatibilities	ASUS™ AURA SYNC, MSI™ MYSTIC LIGHT SYNC, ASROCK™ POLYCHROME SYNC, GIGABYTE™ RGB FUSION
Warrenty	24 Months

Version : 10/2020

* The listed specifications may be altered at any point in time without any pre-notice.

** CHIEFTRONIC® is a registered trade mark. All other brands and/or logos are property of the respective owners.