

- **9 blade reverse design with enhanced air pressure technology**
- **Special fan blades designed for maximum airflow, low-noise & optimal illumination**
- **4-PIN PWM fan-speed control and 3-PIN +5V A-RGB M/B-Sync Technologies supported**

Introducing Chieftec's ZF-1225WRGB-R, featuring a sophisticated 9 blade reverse design engineered with enhanced air pressure technology. Our special fan blades aim to deliver optimal illumination performance with well-balanced maximal airflow and minimal noise disruption.

Take command of your cooling experience with the inclusion of a 4-PIN PWM fan-speed control and seamless compatibility with 3-PIN +5 A-RGB M/B Sync Technologies.

ZF-1225WRGB-R is ready to elevate your setup for an exceptional user experience.



TECHNICAL DATA	
Model	ZF-1225WRGB-R
EAN code	0753263079206
Connector	Fan: 4 pin PWM ; ARGB: 3 pin
Dimension (mm)	120 x 120 x 25
Weight (without/with package)	177g / 188g
Bearing Type	Hydraulic
LED Type	Addressable RGB
LED Lamp	24 pcs (Inner Ring: 8 pcs ; Outer Ring: 16pcs)
Rated Voltage	FAN: DC12V ; LED: DC5V
Rated Current	0.11A
Operating Voltage	10.8V -13.2V
Fan Speed (RPM)	600 - 1600 RPM \pm 10%
Air Flow (CFM)	42.5 CFM
Air Pressure (mmH2O)	1.82 mmH2O
Noise Level (dBA)	26.8 dBA
Scope of delivery	1x 120mm White RGB-R Rainbow fan, 4x Mounting screws
RGB Sync Compatibilities	Support and sync the lighting with: ASUS™ AURA SYNC, MSI™ MYSTIC LIGHT SYNC, ASROCK™ POLYCHROME SYNC, GIGABYTE™ RGB FUSION
Warranty	24 Months

Version: 01/2026

*The listed specifications may be altered at any point in time without any pre-notice.

**Chieftec® is a registered trademark. All other brands and/or logos are property of the respective owners.