

# iARENA SERIES

## GPA-650S // SLEEVED // 650WATT



**Product:** PSU

**Form factor:** PSII

**Color:** silver

The GPA-650S and like all other models in the iARENA Series have a fixed voltage of 230V and are specifically made for Europe. They are the optimal and cost-effective solution for quality-demanding system builders.

**Certificates:**



### Technical data

|                            |                        |
|----------------------------|------------------------|
| <b>Specification:</b>      | ATX 12V 2.3            |
| <b>Efficiency:</b>         | <80%                   |
| <b>Dimensions (DxWxH):</b> | 140mm x 150 mm x 87 mm |
| <b>PCF:</b>                | Active PFC (0,9)       |
| <b>Fan:</b>                | 120mm silent fan       |

### Connectors

| 24 PIN | SATA | Molex | Floppy | 8PIN PCIe (6+2) |
|--------|------|-------|--------|-----------------|
| 1      | 6    | 2     | 1      | 2               |

### DC Output / AC Input

| AC INPUT: 200-240V /4A<br>FREQUENCY: 47Hz-63Hz<br>MAX. LOAD: 650W | DC OUTPUT |       |       |       |       |       |      |              |               |
|---|-----------|-------|-------|-------|-------|-------|------|--------------|---------------|
|   | +5V       | +3,3V | +12V1 | +12V2 | +12V3 | +12V4 | P.F. | -12V         | +5VSB         |
|   | 20A       | 20A   | 50A   | N.A   | N/A   | N/A   | >0,9 | 0,3A<br>3,6W | 2,5A<br>12,5W |
|   | 120W      |       | 600W  |       | N/A   |       |      |              |               |

**Security:** UVP; OVP; SCP; OPP; OCP; OTP; AFC

The listed specifications may be altered at any point in time without any pre-notice. Chieftec® is a registered trade mark. All other brands and/or logos are property of the respective owners.